

KPC 6



KPC6 is an ultra-slim embedded E-box. Provided with rugged metal housing, fanless and ventless design makes it ideal for harsh environments. Various mounting ways facilitate it for KVS, industrial automation, digital signage, POS and more applications.

- Intel® Atom™ embedded computing platform delivers high graphic performance as well as low-power consumption
- Reliable ventless and fanless system
- Ultra compact size
- Flexible mounting support
- Provide most popular I/O ports
- Easy for service design



Features



75 x 75 mm VESA mounting holes in center.



Flush mounting holes on left/right hand sides.



HDD door in bottom for easy service.



External wireless antennas boost the performance in connectivity.

KPC 6

Rugged embedded computer box adapts to different applications.



Specification

Model Name	KPC 6
Motherboard	C36
Processor	Intel® Atom™ N270 processor 1.6GHz L2 512K FSB 533MHz
Chipset	Intel® 945GSE + ICH7M
System Memory	1 x DDR2 DIMM up to 2GB
Graphic Memory	Intel® GMA 950 share system memory up to 224MB
Storage Device	
Hard Drive	1 x 2.5" slim SATA HDD
Flash Memory	1 x pSSD (option)
Expansion	
Mini PCI Slot	1
Front I/O	
Line-out	1 (option)
Antenna Jack	1
Rear I/O	
USB Port	4 x USB 2.0
Serial Port	4 x RJ-45 (COM3 / COM4 with 5V / 12V power)
LAN Port	1 x RJ-45 (10/100/1000Mbps Giga LAN)
VGA	1 x DB-15F
Cash Drawer Port	Support cash drawer 1 x (12V / 24V)
DC Jack	1 x DC-19V
Power LED Indicator	1
Power Button	1
Power	Adapter (DC 65W, 19V, 3.4A)
Certificate	
EMC & Safety	FCC Class A / CE Mark / LVD
Environment	
Operating Temperature	5°C ~ 35°C (41°F ~ 95°F)
Storage Temperature	-20°C ~ 55°C (-4°F ~ 140°F)
Operating Humidity	20% ~ 80% RH non-condensing
Storage Humidity	20% ~ 85% RH non-condensing
Communication	
Wireless LAN	mini PCI-E wireless LAN card 801.11 b/g and antenna (option)
Dimension (W x D x H)	222 x 138 x 36.8 mm / 8.7" x 5.4" x 1.4"
Weight	1.2kg (2.6lbs)
Mounting	100mm x 100mm Standard VESA
OS Supported	Windows® XP Pro, Windows® XP Embedded, Windows® CE, Linux

Product specifications subject to change without prior notice.

©2009 Flytech Technology Co., Ltd. Registered trademarks and trademarks are property of their respective owners. The specification is subject to change without prior notice. Flytech endeavors to ensure that the information in this document is correct and fairly stated but does not accept liability for any error or omissions. The development of Flytech products and services is continuous, and published information may not be up to date. It is important to check the current position with Flytech.



FLYTECH Technology Co., Ltd.
No.168, Sing-ai Rd.,
Neihu District, Taipei City 114,
Taiwan
Tel: 886-2-8791-4988
Fax: 886-2-8791-4966
E-mail: sales@flytech.com.tw
www.flytech.com

U.S.A. - California
47825 Warm Springs Boulevard, Fremont, CA 94539, USA Tel: 1-510-257-5180 Fax: 1-510-257-5181 E-mail: sales@flytech.com
China - Shanghai
3F Building 39, No.333 Qin Jiang Rd., Shanghai 200233, P.R.China
Tel: 86-21-5426-1555 Fax: 86-21-5426-1001 http://www.flytech.com.cn E-mail: sales@flytech.com.cn
China - Hong Kong
Room 01, 6/F, Block A, Tonic Industrial Centre, 26 Kai Cheung Rd., Kowloon Bay, Kowloon, Hong Kong
Tel: 852-3525-5800 Fax: 852-2751-7447 http://www.flytech.com.hk E-mail: sales@flytech.com.hk
Japan - Nagano Ken
2-48-14 Inada, Nagano-Shi, Nagano-Ken, Japan Post Zip Code: 381-0042 Tel: 81-26-259-4804 E-mail: flytech@flytech.co.jp

0909 - KPC6B